

**STANDARD & LIGHTWEIGHT CONCRETE BLOCK / ARCHITECTURAL BLOCK
CUBE SIZES & WEIGHTS**

| STANDARD CONCRETE BLOCK | 10cm | | | 15cm | | | 20cm | | | 25cm | | | 30cm | | |
|----------------------------|--------------------|------------|------|--------------------|------------|------|--------------------|------------|---------|--------------------|------------|--------|--------------------|------------|------|
| | Pieces per Cube | Wt (lbs) | | Pieces per Cube | Wt (lbs) | | Pieces per Cube | Wt (lbs) | | Pieces per Cube | Wt (lbs) | | Pieces per Cube | Wt (lbs) | |
| | | Pce | Cube | | Pce | Cube | | Pce | Cube | | Pce | Cube | | Pce | Cube |
| STANDARD | 120 | 27 | 3240 | 100 | 32 | 3200 | 75 | 40 | 3000 | 67 | 47 | 3149 | 55 | 55 | 3025 |
| SOLID | 120 | 36 | 4320 | 80 | 50 | 4000 | 60 | 70 | 4200 | 39 | 84 | 3276 | 30 | 105 | 3150 |
| SEMI-SOLID | - | - | - | 100 | 39 | 3900 | 75 | 50 | 3750 | 65 | 64 | 4160 | 50 | 72 | 3600 |
| ASHLAR | 240 | 13 | 3120 | 200 | 16 | 3200 | 150 | 19 | 2850 | 130 | 23 | 2990 | 100 | 26 | 2600 |
| BULLNOSE | 120 | 27 | 3240 | 100 | 32 | 3200 | 75 | 40 | 3000 | 67 | 47 | 3149 | 55 | 55 | 3025 |
| HALF BULLNOSE | 240 | 13 | 3120 | 200 | 16 | 3200 | 150 | 22 | 3300 | 130 | 28 | 3640 | 100 | 35 | 3500 |
| BONDBEAM | - | - | - | 100 | 34 | 3400 | 75 | 42 | 3150 | 65 | 50 | 3250 | 50 | 63 | 3150 |
| MODIFIED BOND BEAM | - | - | - | - | - | - | 75 | 42 | 3150 | 65 | 50 | 3250 | 50 | 63 | 3150 |
| KNOCK-OUT | - | - | - | 100 | 28 | 2800 | 75 | 37 | 2775 | 65 | 45 | 2925 | 50 | 53 | 2650 |
| 60% SOLID | - | - | - | - | - | - | 75 | 45 | 3375 | - | - | - | - | - | - |
| 75% SOLID | 120 | 36 | 4320 | 100 | 42 | 4200 | 75 | 56 | 4200 | 52 | 70 | 3640 | 45 | 74 | 3330 |
| PLAIN END | - | - | - | 100 | 32 | 3200 | 75 | 45 | 3375 | 67 | 55 | 3685 | 55 | 65 | 3575 |
| PLAIN HALF | 240 | 13 | 3120 | 200 | 16 | 3200 | 150 | 22 | 3300 | 134 | 28 | 3752 | 100 | 35 | 3500 |
| L-CORNER | 96 | 41 | 3936 | 85 | 46 | 3910 | - | - | - | 60 | 49 | 2940 | 60 | 57 | 3420 |
| BULLNOSE L-CORNER | 96 | 41 | 3936 | 85 | 46 | 3910 | - | - | - | - | - | - | - | - | - |
| 45° CORNER | - | - | - | - | - | - | 100 | 56 | 5600 | 70 | 64 | 4480 | 55 | 72 | 3960 |
| ARCHITECTUAL | 120 | 36 | 4320 | 100 | 37 | 3700 | 75 | 46 | 3450 | 65 | 56 | 3640 | 50 | 66 | 3300 |
| ARCHITECTUAL L-CORNER | 96 | 41 | 4320 | - | - | - | - | - | - | - | - | - | - | - | - |
| LIGHTWEIGHT STANDARD | 120 | 22.6 | 2712 | 100 | 27.85 | 2785 | 75 | 31.75 | 2381.25 | 67 | 38.4 | 2572.8 | 55 | 45 | 2475 |

| | Pieces per Cube | Wt (lbs) | | | Pieces per Cube | Wt (lbs) | |
|---------------|--------------------|------------|------|----------------------------|--------------------|------------|------|
| | | Pce | Cube | | | Pce | Cube |
| 5 CM SOLIDS | 240 | 16 | 3840 | 30CMx30CM QUAD BULLNOSE | 60 | 45 | 2700 |
| 7.5 CM SOLIDS | 180 | 24 | 4320 | BACKUP BRICK | 600 | 5 | 3000 |